

# Instruction Manual

## REWITEC® PowerShot® S/M/L

### Treatment of Gasoline- and Diesel Engines with Products of the REWITEC® PowerShot® family

Thank you for choosing one of our innovative products and we appreciate your confidence in REWITEC®! By using the worldwide approved REWITEC® PowerShot® with the new recipe and patented metal-silicate coating technology, you can amongst others achieve the following:

- ✓ Reduction of fuel consumption
- ✓ Reduction of emissions and harmful particles
- ✓ Longer lifetime
- ✓ Optimization of engine power
- ✓ Reduction of oil consumption
- ✓ Improvement of cold start properties
- ✓ Improvement of engine smoothness

You have definitely stepped into the right direction to protect your engine in the long term, reduce costs at the same time and also contribute positively to the environment. There are various sizes of PowerShot® available (compatible with each other) which are adapted to the size of the engine. Thus for an engine with 5.000 ccm you would use a PowerShot® M (for an engine size of 2.000 ccm) plus a PowerShot® L (for an engine size of 3.000 ccm). In case of any questions or suggestions, please contact us under [support@rewitec.com](mailto:support@rewitec.com) or by telephone +49 6441 44 59 90.

### Application for 4-stroke engines

1. The engine should have operating temperature, but should however run at least for 15 minutes. The REWITEC® PowerShot®-product should have room temperature.
2. Shake well the REWITEC® PowerShot® bottle(s) for about 1 minute.
3. Pour half of the bottle's content into the warm engine oil. Screw on the bottle and shake again for at least 1 minute. Pour in the rest of the content into the engine oil.
4. Subsequently the car should be driven or engine should run for at least 15 minutes.
5. The coating process is finalized after approx. 1.500 kilometer. During this time the oil should not be changed.
6. A retreatment with REWITEC® PowerShot® should take place latest every 2 years or after 20.000 kilometers.

### Application for 2-stroke engines (Motorbikes and Motorboats)

1. The engine should have operating temperature, but should however run at least for 15 minutes. The REWITEC® PowerShot®-product should have room temperature.
2. Shake well the REWITEC® PowerShot® bottle(s) for about 1 minute.
3. Pour half of the bottle's content into the half-filled fuel tank. Screw on the bottle and shake again for at least 1 minute. Pour in the rest of the content into the half-filled fuel tank.
4. The vehicle should be driven or engine should run for at least 15 minutes.
5. A retreatment with REWITEC® PowerShot® should take place latest every 2 years, 400 operating hours or after 20.000 kilometers.

|               |   |
|---------------|---|
| PowerShot® S: | Treatment for cars, motorbikes and motorboats with an engine size up to 600 ccm |
| PowerShot® M: | Treatment for all kind of engines with an engine size up to 2.000 ccm           |
| PowerShot® L: | Treatment for all kind of engines with an engine size up 3.000 ccm              |

#### Safety Advice:

Must not be handled by children. Do not drink the liquid. Avoid skin contact. May be slightly irritating to the eyes. Rinse thoroughly with water and consult a doctor in case the irritation does not disappear. Do not pour into or place next to open fire.

#### Storage Advice:

Products must always be stored upright! Please store at room temperature.  
Best before: see lid.